

TECHNICAL DATA

OUTSIDE DIAMETER OF ELECTRICAL CONDUIT/STEEL PIPE						
SIZE	EMT		IMC		RIGID/STEEL PIPE	
	DECIMAL	FRACTION	DECIMAL	FRACTION	DECIMAL	FRACTION
1/2	0.706	11/16	0.815	13/16	0.840	13/16
3/4	0.922	15/16	1.029	1	1.050	1-1/16
1	1.163	1-3/16	1.290	1-5/16	1.315	1-5/16
1-1/4	1.510	1-1/2	1.638	1-5/8	1.660	1-11/16
1-1/2	1.740	1-3/4	1.883	1-7/8	1.900	1-7/8
2	2.197	2-3/16	2.360	2-3/8	2.375	2-3/8
2-1/2	2.875	2-7/8	2.857	2-7/8	2.875	2-7/8
3	3.500	3-1/2	3.476	3-1/2	3.500	3-1/2
3-1/2	4.000	4	3.971	4	4.000	4
4	4.500	4-1/2	4.466	4-7/16	4.500	4-1/2
5	-	-	-	-	5.563	5-9/16

TBNB TIP:

"Universal clamps can be used with both
EMT and RIGID pipe
- BUT -
for the best possible fit, specify either EMT
or RIGID sizes."



OUTSIDE DIAMETER OF COPPER TUBE		
NOMINAL SIZE	TYPE M, L, K	
	DECIMAL	FRACTION
1/4"	0.375	3/8
3/8"	0.500	1/2
1/2"	0.625	5/8
3/4"	0.875	7/8
1"	1.125	1-1/8
1-1/4"	1.375	1-3/8
1-1/2"	1.625	1-5/8
2"	2.125	2-1/8
2-1/2"	2.625	2-5/8
3"	3.125	3-1/8
3-1/2"	3.625	3-5/8
4"	4.125	4-1/8
5"	5.125	5-1/8
6"	6.125	6-1/8
8"	8.125	8-1/8